

**Amendment to the Claims**

Listing of Claims:

21. (Previously Added) A drumbar apparatus for use in removal and replacement of brake drums mounted on a spoked wheel of a vehicle; the spoked wheel having a frontside, a backside and an axle housing extending therethrough; said drumbar apparatus comprising:

an elongated intermediate portion for insertion thorough the axle housing of the spoked wheel and having opposite ends;

a wrench end portion at one end of the intermediate portion and extending at an angle of about 102 degrees therefrom;

an anti-slip handle at the other end of the intermediate portion and extending in the opposite direction from and substantially parallel to the wrench end portion;

a socket mounting member having a spring-urged detent, the socket mounting member being mounted at a distal end of the wrench end portion and extending perpendicular thereto in a direction toward the handle;

a socket on the socket mounting member; and

the wrench end and intermediate portion constructed and

In re: Tremblay et al.  
Filed: October 31, 2000  
Serial No. 09/702,957  
Page 5

arranged for insertion through the axle housing of the spoked wheel for engaging the socket with a nut or bolt head on the backside of the spoked wheel so that a user can hold the nut or bolt head while utilizing another wrench at the frontside of the spoked wheel to remove or retighten a bolt to remove and replace a brake drum mounted on the backside of the spoked wheel.